



XPS-F



XPS

Application Limits

- ◉ Liquid temperature: +2°C ~ +110°C
- ◉ Maximum ambient temperature +40°C
- ◉ Maximum system pressure 10bar
- ◉ Protection level: IP44
- ◉ Mains connection: 220V/50Hz, 220V/60Hz, 127V/60Hz
- ◉ Insulation class: H
- ◉ Pumped liquid characteristics: clean, free from solids and mineral oils, non-toxic, chemically neutral, close to the characteristics of water
- ◉ Installation: the motor shaft must be kept in horizontal direction
- ◉ pH: 6.5 to 8.5

Features

- ◉ 3-speed adjustment
- ◉ Low noise
- ◉ No leakage

Performance Data

Model	Speed	Input Power P _i (W)	Current (A)			Capacitor		Pipe Distance (mm)	Max. head (m)	Whole lift (m)	Max. flow (m ³ /h)	Inter Box			Outer Box		20" Loading Qty (pcs)
			220V 50Hz	220V 60Hz	127V 60Hz	μF/450V	μF/250V					G.W. (kg)	Packing Dim. (mm)	PCS/CTN	Packing Dim. (mm)	G.W. (kg)	
						220V 50Hz/60Hz	127V/60Hz										
XPS15-4-130	3	60	0.26	/	/	2	/	130	4	0~4	2	2.5	150x130x140	8	320x280x300	21	6664
	2	45	0.20	/	/	2	/										
	1	30	0.13	/	/												
XPS15-5-130	3	80	0.34	/	/	2.5	/	130	5	0~5	2	2.4	150x130x140	8	320x280x300	22	6664
	2	55	0.24	/	/	2.5	/										
	1	35	0.15	/	/												
XPS15-6-130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	2	2.8	180x120x135	8	380x260x290	23	5880
	2	65	0.30	0.30	0.65												
	1	45	0.20	0.20	0.41												
XPS15-9-140	3	120	0.48	0.48	0.83	3	10	140	9	0~9	1.6	2.8	180x120x135	8	380x260x290	23	5880
	2	85	0.38	0.38	0.66												
	1	60	0.26	0.26	0.45												
XPS20-4-130	3	60	0.26	/	/	2	/	130	4	0~4	2.2	2.4	150x130x140	8	320x280x300	22	6664
	2	45	0.20	/	/	2	/										
	1	30	0.13	/	/												
XPS20-5-130	3	80	0.34	/	/	2.5	/	130	5	0~5	2.2	2.4	150x130x140	8	320x280x300	22	6664
	2	55	0.24	/	/	2.5	/										
	1	35	0.15	/	/												
XPS20-6-130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	2.2	2.8	180x120x135	8	380x260x290	23	5880
	2	65	0.30	0.30	0.65												
	1	45	0.20	0.20	0.41												
XPS25-4-130	3	60	0.26	/	/	2	/	130	4	0~4	3	3.0	150x130x140	8	320x280x300	25	6664
	2	45	0.20	/	/	2	/										
	1	30	0.13	/	/												
XPS25-5-130	3	80	0.34	/	/	2.5	/	130	5	0~5	3	3.0	150x130x140	8	320x280x300	25	6664
	2	55	0.24	/	/	2.5	/										
	1	35	0.15	/	/												
XPS25-6-130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	3	3.0	150x130x140	8	320x280x300	25	6664
	2	65	0.30	0.30	0.65												
	1	45	0.20	0.20	0.41												
XPS25-4-180	3	60	0.26	/	/	2	/	180	4	0~4	3	3.0	200x130x155	8	420x280x330	26	4800
	2	45	0.20	/	/	2	/										
	1	30	0.13	/	/												
XPS25-5-180	3	80	0.34	/	/	2.5	/	180	5	0~5	3	3.0	200x130x155	8	420x280x330	26	4800
	2	55	0.24	/	/	2.5	/										
	1	35	0.15	/	/												
XPS25-6-180	3	90	0.40	0.40	0.80	2.5	6	180	6	0~6	3	3.0	200x130x155	8	420x280x330	26	4800
	2	65	0.30	0.30	0.65												
	1	45	0.20	0.20	0.41												
XPS32-4-180	3	60	0.26	/	/	2	/	180	4	0~4	3.5	3.6	200x130x155	8	420x280x330	30	4800
	2	45	0.20	/	/	2	/										
	1	30	0.13	/	/												
XPS32-5-180	3	80	0.34	/	/	2.5	/	180	5	0~5	3.5	3.6	200x130x155	8	420x280x330	30	4800
	2	55	0.24	/	/	2.5	/										
	1	35	0.15	/	/												
XPS32-6-180	3	90	0.40	0.40	0.80	2.5	6	180	6	0~6	3.5	3.6	200x130x155	8	420x280x330	30	4800
	2	65	0.30	0.30	0.65												
	1	45	0.20	0.20	0.41												
XPS20-12-180	3	245	1.04	1.04	1.80	6	20	180	12	0~12	3	4.8	200x160x180	4	420x340x200	20	3200
	2	210	0.92	0.92	1.60												
	1	140	0.63	0.63	1.10												
XPS25-8-180	3	200	0.83	0.83	1.63	6	15	180	8	0~8	7	5.0	200x160x180	4	420x340x200	20	3200
	2	185	0.78	0.78	1.56												
	1	145	0.62	0.62	1.28												
XPS25-12-180	3	245	1.04	1.04	1.80	6	20	180	12	0~12	3.5	5.4	200x160x180	4	420x340x200	21	3200
	2	210	0.92	0.92	1.60												
	1	140	0.63	0.63	1.10												
XPS32-8-180	3	245	1.04	1.04	1.80	6	/	180	8	0~8	10	5.4	200x160x180	4	420x340x200	23	3200
	2	210	0.92	0.92	1.60												
	1	140	0.63	0.63	1.10												
XPS32-5F-220	3	145	0.65	/	/	4	/	220	5	0~5	8	/	/	/	305x165x205	10.5	2160
	2	135	0.60	/	/												
	1	95	0.45	/	/												
XPS32-8F-220	3	245	1.04	1.04	1.80	6	/	220	8	0~8	10	/	/	/	305x165x205	11	2160
	2	210	0.92	0.92	1.60												
	1	140	0.63	0.63	1.10												

*Types with "/" can be developed according to need.